



Galo Energy Pvt.Ltd.

TUBULAR LEAD ACID BATTERY



www.galo.co.in

- ▶ 2500+ Cycle Life
- ▶ Meets Govt. Norms
- ▶ Excellent Battery Back-Up
- ▶ Long Service Life
- ▶ High Grade Polymers
- ▶ Low Weight - High Performance



Environment
Friendly

ISO
9001 - 2008
14001 - 2004

Max Protection
BMS

100%
MADE IN
INDIA

✉ info@galo.co.in

☎ +91 9310141976 | +91 9310341987



TUBULAR LEAD ACID BATTERY

GTT 40Ah-150Ah

MODEL	GTT 40	GTT 75	GTT 120	GTT 150
Total number of elements of 2V	6	6	6	6
Nominal voltage of the unit element	12	12	12	12
Nominal voltage of the battery	12	12	12	12
Capacity C10 of the unitary element (at 20°C up to 1.80 V/él.)	40AH	75AH	120AH	150AH
Capacity C10 of the battery (at 20°C up to 1.80 V/él.)	40AH	75AH	120AH	150AH
Depth of Maximum Discharge (DOD)	80%	80%	80%	80%
Number of cycles to 20% DOD	10000	10000	10000	10000
Number of cycles to 50% DOD	3500	3500	3500	3500
Number of cycles to 80% DOD	1000	1000	1000	1000
LENGTH±3	410	510	520	520
WIDTH±3	174	190	280	280
HEIGHT ±3	245	290	300	300
WEIGHT ± 1.00 KG	23.000	34.500	56.500	58.000
CONTAINER AS PER JIS	N 100	N 120	IT 500	IT 500
	-	-	N 200 JUMBO	N 200 JUMBO

GTT 160Ah-250Ah

MODEL	GTT 160	GTT 180	GTT 200	GTT 250
Total number of elements of 2V	6	6	6	6
Nominal voltage of the unit element	12	12	12	12
Nominal voltage of the battery	12	12	12	12
Capacity C10 of the unitary element (at 20°C up to 1.80 V/él.)	160AH	180AH	200AH	250AH
Capacity C10 of the battery (at 20°C up to 1.80 V/él.)	160AH	180AH	200AH	250AH
Depth of Maximum Discharge (DOD)	80%	80%	80%	80%
Number of cycles to 20% DOD	10000	10000	10000	10000
Number of cycles to 50% DOD	3500	3500	3500	3500
Number of cycles to 80% DOD	1000	1000	1000	1000
LENGTH±3	520	510	510	510
WIDTH±3	280	190	190	190
HEIGHT ±3	300	410	410	410
WEIGHT ± 1.00 KG	60.000	67.000	72.500	75.000
CONTAINER AS PER JIS	IT 500	IT 500	IT 500	IT 500